

Fasson Print - datapol white

Face Stock

A matt white polyester film with a toner receptive coating.	Basis Weight	ISO 536	g/m ²	76
	Caliper	ISO 534	mm	0,06

Adhesive

A permanent acrylic based adhesive.	Initial Tack	FTM 9 glass	N/m	400
	Peel Adhes. 90°	FTM 2 st.st.	N/m	300
	Min. appl. Temp.		°C	0
	Service temp		°C	-20 / +120

Adhesive performance

A permanent acrylic based adhesive which features excellent clarity and UV resistance.

Liner

A white, one side clay coated bleached kraft paper.	Basis Weight	ISO 536	g/m ²	98
	Caliper	ISO 534	mm	0,11
Laminate	Total Caliper	mm	0,19	+/-10%

Applications and use

Fasson Print datapol white is specifically designed for "hot fuse" sheet fed and continuous laser printing, providing optimal flatness during conversion, storage and laser printing processing.

Some slight curl may be seen on exiting the user but this will flatten quickly.

Enduse is mainly in the area of "long life" durable, tracking labels i.e. bar coding and nameplates in the "white" and "brown" goods markets.

Being relatively rigid, the film will not conform well to non-uniform or complex shaped surfaces.

Shelf life

Two years, stored at 22°C / 50% RH.

This issue replaces all previous issues.

The specifications given above are based on existing findings and empirical values. It is the user's own responsibility to check, prior to use, whether the product is in fact suitable for the intended application, and with particular reference to any influential factors peculiar to the application for which the product is to be used. All matters relating to our guarantee and liability in respect of the above product, including the period of guarantee, are governed by our currently valid General Conditions of Sale in so far as these conditions do not contravene any overriding legislation. Subject to technical changes and improvements without prior notice.

